













Petroleum Hoses

	Description	Temp. Range	Size	Pressure
DISCHARGE - SMOOTH				
	Fuel Discharge Discharge hose for gasoline, oil, ethanol blends and other petroleum based products with up to 50% aromatic content. Antistatic wires for conductivity.	-35°F - 180°F	3/4" - 6"	150 PSI
SUCTION AND DISCHARGE - SMOOTH				
	Prospector Petro A flexible and lightweight hose for use in tank truck and drilling operations to transfer diesel, ethanol, gasoline, oil and petroleum-based products with up to 50% aromatic content. Available with red cover as well.	-25°F - 180°F	1" - 6"	150 PSI
	Flexwing Petroleum This durable, oil-resistant hose sets the standard for transfer hose service. It is used in tank truck and in-plant operations to transfer gasoline, oil, ethanol blends and other petroleum base products with up to 50% aromatic content. Available with red cover as well.	-35°F - 200°F	1/4" - 6"	150 PSI
	Arctic Flexwing The most popular suction and discharge hose for gasoline, oil & other petroleum products. To be used in cold temperature up to -65°F (-54°C).	-65°F - 180°F	1/4" - 2 1/2"	150 PSI
	Flexwing Versafuel The right hose to transfer diesel, biodiesel blends, B-100, ethanol blends, gasoline, oil and petroleum base products up to 60% aromatic content. Available with corrugated cover as well.	-30°F - 180°F	1/4" - 2 1/2"	150 PSI
	Prospector Petro 300 High pressure hoses for use in tank truck and in-plant operations to transfer gasoline, oil, ethanol blends and other petroleum base products up to 50% aromatic content. Designed for pressure, gravity flow, or full-suction service.	-25°F - 180°F	1" - 6"	300 PSI
	Super Black Flexwing 300 A premium high pressure petroleum transfer hose for handling ethanol blends, gasoline, oils and other petroleum products up to 50% aromatic content. Maximum working pressure of 300 PSI. 400 PSI version available, too.	-35°F - 200°F	3/4" - 6"	300 PSI
SUCTION AND DISCHARGE - CORRUGATED				
	LW Arctic Tank Truck For transfer of petroleum-based products under suction, low-pressure discharge or gravity flow. Heavier duty service when compared to the Arctic ExtremeFlex. Flexibility maintained down to -65°F (-54°C). 200 PSI Version also available.	-65°F - 180°F	2" - 4"	150 PSI
	Prospector Flex Petro 150 For use in tank trucks and in-plant operations to transfer gasoline, oil ethanol blends and other petroleum-based products up to 50% aromatic content.	-35°F - 180°F	1" - 6"	150 PSI
	Red Flextra For the transfer of ethanol blends, gasoline and other petroleum-based products under pressure, gravity flow or full-suction where maximum flexibility is needed. 100 PSI version available, too.	-30°F - 180°F	1 1/2" - 4"	150 PSI
	ExtremeFlex Petroleum Extremely flexible and lightweight drop hose for use in tank truck and in-plant operation to transfer diesel, ethanol, gasoline, oil and petroleum-based products with up to 50% aromatic content. It has a corrugated construction for lower drag coefficient and superior abrasion resistance. Available with red cover as well.	-35°F - 200°F	3/4" - 6"	150 PSI
	Arctic ExtremeFlex 150 Blue An extremely flexible and lightweight drop hose for transfer of petroleum-based products under suction, low-pressure discharge or gravity flow in cold environment.	-65°F - 180°F	1 1/2" - 4"	150 PSI

Ask us about our Patented Insta-Lock™ Crimped Fittings



More petroleum hoses are available from Continental. For further information reach out to our Customer Service or your sales representative.

Copyright © 2019 ContiTech AG. All rights reserved. For complete information go to: www.contitech.de/disc/en