PetroDEF Hose & Fittings Durable Diesel Exhaust Fluid connections solved!

The world of DEF hose and fitting connections can be confusing when having to understand what end connection you need to replace your existing products and what hose is best suited for the application! Fluid Hose has expanded on their line PetroDEF™ fittings to now include hose as well!

Available in bulk form or pre-assembled. See next page for more details.



- Branded "DEF"
- Satisfies standard ISO 22241

New



PetroDEF[•] Fittings

- 3/4" Male NPT or BSPP solid or swivels •
- 3/4" and 1" female BSPP •
- 2piece "inter-locked" crimp & Reusable
- 304 Stainless Steel
- Peroxide cured EPDM O-rings
- **Grooved Ferrules**





Mississauga: (905) 670-0955 Hamilton: (905) 296-7515 Web: www.fluidhose.com Email: sales@fluidhose.com

PetroDEF Hose

New!

100 TELL 2011 QUALITUM/DEF-D DEF DISPENSING HOSE 314" 250 PSI MAX WP / ISO 2224

Tube: Peroxide Cured EPDM Synthetic Rubber
Reinforcement: 1 Textile Braid
Cover: Wrapped EPDM Rubber. Weather, UV and Ozone Resistant
Temp: -40°F (40°C) to +176°F (80°C)
Safety Factor: 4:1
Package: Plastic reels, cut length or pre-assembled
Color: Black (Blue available with production run MOQ)

Branding: White Text "DEF Dispensing ISO 22241"

	I.I	D.	O.D.		W.P.	Weight		Min Bend
Part #	(in)	(mm)	(in)	(mm)	PSI	Lbs/ft	Kg/ft	(in)
IDEFDSP-BLK-12	3/4	19.0	1.130	28.7	250	0.14	0.06	2.0

PetroDEF Fittings











Tube: 304 Stainless Steel O-rings: Peroxide Cured EPDM

Style: 2 Piece Inter-Lock. Intended for a 1-1/8" Hose OD Range

Part #	Hose Size (in)	Connection Size (in)	Connection Type
DEF-MP-12-12	3/4	3/4	Male NPT Solid
DEF-MP-SW-12-12	3/4	3/4	Male NPT Swivel
DEF-MBSPP-12-12	3/4	3/4	Male BSPP Solid
DEF-MBSPP-SW-12-12	3/4	3/4	Male BSPP Swivel
DEF-FBSPP-SW-12-12	3/4	3/4	Female BSPP Swivel
DEF-FBSPP-SW-12-16	3/4	1	Female BSPP Swivel
DEF-RU-MP-SW-12-12	3/4	3/4	Re-Usable Male NPT Swivel
DEF-RU-MBSPP-SW-12-12	3/4	3/4	Re-Usable Male BSPP Swivel



Mississauga: (905) 670-0955 Hamilton: (905) 296-7515 Web: www.fluidhose.com Email: <u>sales@fluidhose.com</u>