

# NEW! Quantum Versa-Lock™

## General Purpose Push On Hose



### Versa-Lock™ Applications

- Perfect hose when **quick installation** is required using push-on fittings at maximum working pressures of 300 PSI . **No clamping or crimping required for air and water** applications.
- For **low-pressure hydraulic applications** the hose can be crimped with hydraulic grade fittings (consult Fluid Hose for more information)
- **General** industrial, maintenance and automotive assembly applications

Part #	I.D.		O.D.		Working Pressure		Weight		Min Bend Radius	Pkg Qty	
	(XXX = color)	(in)	(mm)	(in)	(mm)	PSI	(Bar)	Lbs/ft			Kg/ft
IGPPO-300-XXX-04		1/4	6.7	0.496	12.6	300	20	0.09	0.04	3.0	300
IGPPO-300-XXX-06		3/8	9.8	0.630	16	300	20	0.11	0.05	3.0	300
IGPPO-300-XXX-08		1/2	12.8	0.748	19	300	20	0.14	0.06	5.0	300
IGPPO-300-XXX-10		5/8	16	0.921	23.4	300	20	0.21	0.09	6.0	300
IGPPO-300-XXX-12		3/4	19	1.102	28	300	20	0.29	0.13	7.0	200
IGPPO-300-XXX-16		1	25.4	1.370	34.8	300	20	0.41	0.19	8.0	200

**Tube:** NBR Class A Oil Resistant Synthetic Rubber

**Reinforcement:** 1 Textile Braid

**Cover:** Smooth NBR/PVC Class B Oil, Weather Resistance, MSHA, Non-Conductive

**Temp:** -40°C (40°F) to +100°C (212°F)

+85°C (+185°F) Max For Water

+70°C (+158°F) Max For Air

**Burst Pressure Ratio:** 4:1

**Branding:** White Letters

**Package Type:** Multi-piece reels (cut length available in coils)

**Other:** Not recommended for use with Steam or Refined Fuels

### Colors

BLK	
BLU	
RED	
GRN	
GRA	
PUR	
YEL	